

## SMA Female to BNC Female Bulkhead Adapter



## TECHNICAL DATA SHEET

PE9185

## SMA Female to BNC Female Bulkhead Adapter

Configuration

Connector 1 SMA Female
Connector Specification 1 MIL-STD-348
Connector 2 BNC Female
Adapter Design Standard
Body Style Straight
Mount Method Bulkhead

**Electrical Specifications** 

Frequency Range, GHz

Impedance, Ohms

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

Dielectric Withstanding Voltage, Vrms

**Mechanical Specifications** 

**Temperature** 

Operating Range,deg C -65 to +165

Size

 Length, in [mm]
 1.32 [33.53]

 Width/Dia., in [mm]
 0.69 [17.53]

 Dielectric Type
 Teflon

**Connector 1** 

Type SMA Female

Inner Conductor Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel

Connector 2

Type BNC Female

Inner Conductor Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-bnc-female-straight-adapter-pe9185-p.aspx

SMA Female to BNC Female Bulkhead Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9185 CAD Drawing
SMA Female to BNC Female Bulkhead Adapter

