

产品型号 type	L
SMC-JYD1	24.3
SMC-JYD2	20.0

Electrical Characteristics:

1. Characteristic Impedance: 50Ω
2. Frequency range: DC~10GHz
3. Contact resistance
Center conductor: $\leq 6.0 \text{ m}\Omega$
Out conductor: $\leq 1.0 \text{ m}\Omega$
4. Insulation resistance: $\geq 1000 \text{ M}\Omega$
5. Insulator withstanding: 750V
6. Durability: 5000cycles

主要性能指标:

1. 特性阻抗: 50Ω
2. 频率范围: DC~10GHz
3. 接触电阻:
中心导体: $\leq 6.0 \text{ m}\Omega$
外导体: $\leq 1.0 \text{ m}\Omega$
4. 绝缘电阻: $\geq 1000 \text{ M}\Omega$
5. 介质耐压: 750V
6. 插拔次数: 5000次

Application: MIL-C-39012/73A


执行标准: MIL-C-39012/73A

Material&Finishing

1. Center contact:
Male: phosphor bronze, gold plated
2. Bodies: brass, gold plated
3. Insulators: PTFE

材料和镀层

1. 中心接触件:
插针: 锡磷青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

	SCALE	<p>SMC-JYD1 RF COAXIAL CONNECTOR</p>	<p>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±</p>
	4:1		
	NAME	DATE	
DRAWN			
CHECKED			
APPROVED			

西安富士达科技股份有限公司
XI'AN FORSTAR S&T CO.,LTD.