



N Male to 7/16 DIN Male LSZH Jacketed Low PIM  
Cable Using SR401FLJ Low PIM Coax, RoHS

TECHNICAL DATA SHEET

PE3C2012

Pasternack's Low PIM formable cable assemblies are built using high quality formable .141 and .250 inch filled braid coax. These low PIM cable assemblies offer excellent Passive Intermodulation performance of -160dBc and are 100% RF and PIM tested at the time of production. Our low PIM cables use a protective Low Smoke Zero Halogen PVC jacket material and make it ideal for environments where safety and reliability is needed. There are 26 low PIM cable assembly configurations available including 4.1/9.5 Mini DIN, 7/16 DIN, Type N and SMA series in 100cm and 200cm standard lengths.

**Features**

- 0.141 and 0.250 Formable cable
- LSZH (Low Smoke Zero Halogen) PVC Jacket
- -160 dBc for Type N, 4.1/9.5 DIN, 7/16 DIN version
- -150 dBc for SMA versions
- > -100 dB RF Shielding
- DC to 3 GHz and DC to 6 GHz configurations
- 100% PIM and RF tested

**Applications**

- Communication connectivity requirements
- Low PIM applications
- Test equipment and rack systems
- Low PIM Lab Testing

**Configuration**

Connector 1	N Male
Connector 2	7/16 DIN Male
Cable Type	PE-SR401FLJ Low PIM

**Electrical Specifications**

Frequency Range	DC to 3 GHz
Impedance	50 Ohms
Max VSWR	1.15:1
RF Shielding	-100 dB
Max Input Power	2 KWatts
Passive Intermodulation	-160 dBc

**Performance by Frequency**

**Frequency 1**

Frequency	500 MHz
Insertion Loss	0.05 dB/ft [0.16 dB/m]
Power Handling, KWatts	2

**Frequency 2**

Frequency	1000 MHz
Insertion Loss	0.08 dB/ft [0.26 dB/m]
Power Handling	1.5 KWatts

**Frequency 3**

Frequency	3 GHz
Insertion Loss	0.14 dB/ft [0.46 dB/m]
Power Handling	950 Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to 7/16 DIN Male LSZH Jacketed Low PIM Cable Using SR401FLJ Low PIM Coax, RoHS PE3C2012](#)



N Male to 7/16 DIN Male LSZH Jacketed Low PIM  
Cable Using SR401FLJ Low PIM Coax, RoHS

TECHNICAL DATA SHEET

PE3C2012

**Mechanical Specifications**

**Temperature**

Temperature Operating Range -55 to +125 deg C

**Size**

One Time Minimum Bend Radius 5 in [127 mm]

**Cable**

Cable Type PE-SR401FLJ Low PIM  
Cable Inner Conductor Copper, Silver  
Cable Outer Conductor Copper, Tin  
Dielectric Type PTFE  
Jacket Material PVC LSZH  
Jacket Diameter 0.276 in [7.01 mm]

**Connector 1**

Type N Male  
Configuration Straight  
Inner Conductor Material and Plating Brass, Silver  
Coupling Nut Material and Plating Brass, Tri-Metal  
Hex Size 3/4 inch  
Body Material and Plating Brass, Silver  
Dielectric Type PTFE

**Connector 2**

Type 7/16 DIN Male  
Configuration Straight  
Inner Conductor Material and Plating Brass, Silver  
Coupling Nut Material and Plating Brass, Tri-Metal  
Hex Size 1 1/4 inch  
Body Material and Plating Brass, Silver  
Dielectric Type PTFE

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

RoHS Compliant Yes

**Plotted and Other Data**

Notes:

- Values at +25 °C, sea level

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to 7/16 DIN Male LSZH Jacketed Low PIM Cable Using SR401FLJ Low PIM Coax, RoHS PE3C2012](#)



N Male to 7/16 DIN Male LSZH Jacketed Low PIM  
Cable Using SR401FLJ Low PIM Coax, RoHS

TECHNICAL DATA SHEET

PE3C2012

**How to Order**

Part Number Configuration:

**PE3C2012**

- xx

uu

Unit of Measure:  
cm = Centimeters  
<blank> = Inches  
Length  
Base Number

Example: PE3C2012-12 = 12 inches long cable  
PE3C2012-100cm = 100 cm long cable

N Male to 7/16 DIN Male LSZH Jacketed Low PIM Cable Using SR401FLJ Low PIM Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [N Male to 7/16 DIN Male LSZH Jacketed Low PIM Cable Using SR401FLJ Low PIM Coax, RoHS PE3C2012](#)


URL: <http://www.pasternack.com/n-male-7-16-male-sr401flj-low-pim-cable-assembly-pe3c2012-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE3C2012 CAD Drawing

N Male to 7/16 DIN Male LSZH Jacketed Low PIM Cable

Using SR401FLJ Low PIM Coax, RoHS



- NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.

3. DIMENSIONS ARE IN INCHES [mm].

4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $3/8"$ , WHICHEVER IS GREATER.

DWG TITLE		FSCM NO. 53919	
PE3C2012		CAD FILE	120314
		SCALE	N/A
		SIZE	A
			2233

PE

PASTERNAK®

THE ENGINEER'S RF SOURCE

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: [www.pasternack.com](http://www.pasternack.com) | E-Mail: [sales@pasternack.com](mailto:sales@pasternack.com)