


剥线尺寸
stripping dimension



产品型号 type	电缆型号 cable type
N-K5YA	SFF-50-3-1、RG-141A/U、RG-58C/U

Electrical Characteristics:

1. Characteristic Impedance: $50\ \Omega$
2. Frequency range: DC~6Ghz
3. Contact resistance
Center conductor: $\leq 1.0\ m\Omega$
Out conductor: $\leq 0.2\ m\Omega$
4. Insulation resistance: $\geq 5000M\Omega$
5. Insulator withstanding: 1500V
6. VSWR: ≤ 1.5
7. Durability: 500cycles

主要性能指标:

1. 特性阻抗: $50\ \Omega$
2. 频率范围: DC~6Ghz
3. 接触电阻:
中心导体: $\leq 1.0\ m\Omega$
外导体: $\leq 0.2\ m\Omega$
4. 绝缘电阻: $\geq 5000M\Omega$
5. 介质耐压: 1500V
6. 电压驻波比: ≤ 1.5
7. 插拔次数: 500次

Application: MIL-C-39012/1E

执行标准: MIL-C-39012/1E

Material&Finishing

1. Center contact :
Female: phosphor bronze, gold plated
2. Bodies: brass, nickel plated
3. Crimp ferrule: copper, nickel plated
4. Insulators: PTFE

材料和镀层

1. 中心接触件:
插孔: 锡磷青铜, 镀金
2. 壳体: 黄铜, 镀镍
3. 线夹: 黄铜, 镀镍
4. 绝缘子: 聚四氟乙烯

 	SCALE		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES $.X \pm .15$ $\pm 1^\circ$ $.XX \pm .05$ $.XXX \pm$
	1.5:1		
NAME		DATE	N-K5YA RF COAXIAL CONNECTOR 西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.
DRAWN			
CHECKED			
APPROVED			