



安装开孔
mounting hole

Electrical Characteristics:

1. Characteristic Impedance: 50Ω
2. Frequency range: DC~11Ghz
3. Contact resistance
Center conductor: $\leq 1.0 \text{ m}\Omega$
Out conductor: $\leq 0.2 \text{ m}\Omega$
4. Insulation resistance: $\geq 5000 \text{ M}\Omega$
5. Insulator withstanding: 1500V
6. Durability: 500cycles

主要性能指标:

1. 特性阻抗: 50Ω
2. 频率范围: DC~11Ghz
3. 接触电阻:
中心导体: $\leq 1.0 \text{ m}\Omega$
外导体: $\leq 0.2 \text{ m}\Omega$
4. 绝缘电阻: $\geq 5000 \text{ M}\Omega$
5. 介质耐压: 1500V
6. 插拔次数: 500次

Application: MIL-C-39012/1E

Material&Finishing

1. Center contact:
brass, gold plated
2. Bodies and other metal parts:
brass, nickel plated
3. Insulators: PTFE

执行标准: MIL-C-39012/1E

材料和镀层

1. 中心接触件:
黄铜, 镀金
2. 壳体和其它金属零件:
黄铜, 镀镍
3. 绝缘子: 聚四氟乙烯

		SCALE	1:1	N-KKD	RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES X± .15 .XX± .05 XXX±
DRAWN	NAME	DATE				
CHECKED						
APPROVED						
西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.						