

Xtra Long Life SPDT Switch

50Ω DC to 18 GHz 24 Volt

Features

- low insertion loss, 0.25 dB typ.
- high isolation, 85 dB typ.
- high power handling, 10W
- ultra reliable
- break-before-make configuration
- reflective failsafe switch
- protected by US Patents 5,272,458; 6,414,577; 6,650,210; 7,633,361; 7,843,289 6,650,210; 7,633,361; 7,843,289

Applications

- (ATE) automatic test equipment
- reliable "sleep-time" switching
- redundancy switching for microwave radio

MSP2T-18XL+ MSP2T-18-PM+ MSP2T-18-BM+



MSP2T-18XL+



MSP2T-18-PM+
Panel Mount



MSP2T-18-BM+
Base Mount



Model No.	Connectors	Bracket Option	Case Style	Price	Qty.
MSP2T-18XL+	SMA	—	FK811	\$159.95	(1-9)
MSP2T-18-PM+	SMA	Panel Mount	FK811-PM	\$162.95	(1-9)
MSP2T-18-BM+	SMA	Base Mount	FK811-BM	\$162.95	(1-9)

See Page 2 for Mounting Options Available
Option must be specified when ordering

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

Parameter	Condition	Min.	Typ.	Max.	Unit
Frequency Range		DC	—	18	GHz
Insertion Loss	DC - 1 GHz	—	0.10	0.15	dB
	1 - 8	—	0.20	0.30	
	8 - 12	—	0.25	0.35	
	12 - 18	—	0.30	0.45	
Isolation	DC - 1 GHz	85	100	—	dB
	1 - 8	75	90	—	
	8 - 12	70	80	—	
	12 - 18	60	66	—	
VSWR	DC - 1 GHz	—	1.05	1.10	:1
	1 - 8	—	1.20	1.35	
	8 - 12	—	1.20	1.35	
	12 - 18	—	1.15	1.40	
DC Current	at 24V	—	80	115	mA
RF Power Cold Switching ⁴	DC - 18 GHz	—	—	10	W
RF Power Hot Switching	Note 1	—	—	0.1	W
	Note 2	—	—	1.0	

Additional Specifications

Operating Voltage Range	24V (nom) ±1V
Switching Time (Typ.)	20ms
Life ³ (Min.)	1 year/10 million cycles

Notes

1. To achieve specified life, hot switching RF power must not exceed this level.
2. Degradation in life (min.) to typically 3 million switch cycles for hot switch at this RF power level.
3. Tested at 0 dBm RF power.
4. Power handling is specified with RF applied to the IN port and output load connected to either J1 or J2.

Maximum Ratings

Operating Temperature	-15°C to +45°C
Storage Temperature	-15°C to +85°C
RF Power (at IN port)	10W
RF Power (at J1 and J2)	1W
Control Voltage	26VDC

Permanent damage may occur if any of these limits are exceeded.


**10 YEAR EXTENDED
WARRANTY**

10 Yr. 100 Million Cycles*
\$19.95/yr.
for a total of
\$199.50


*10 year agreement
required
Click Here for
details

Switching States

DE-ENERGIZED DC=0V




ENERGIZED DC=24V



MSP2T-18XL+ MSP2T-18-PM+ MSP2T-18-BM+


Outline Drawing (FK811)



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt
2.00	1.34	.50	.045	1.240	.170	.445	.440	.103	.070	.120	.230	.440	.25	.24	.297	.740	.19	grams
50.80	34.04	12.70	1.14	31.50	4.32	11.30	11.18	2.62	1.78	3.05	5.84	11.18	6.35	6.10	7.54	18.80	4.83	41.0


Marking Drawing



MSP2T-18XL+




Outline Drawing (FK811-PM) Panel Mount Bracket



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	wt
2.00	1.34	.50	.670	.440	.25	.24	.297	.740	.19	2.14	.094	1.78	0 MIN / .50 MAX	.22	#4-40	grams
50.80	34.04	12.70	17.02	11.18	6.35	6.10	7.54	18.80	4.83	54.36	2.39	45.21	0 MIN / 6.35 MAX	5.59	(-)	64.2


Marking Drawing



**MSP2T-18-PM+
Panel Mount Option**




Outline Drawing (FK811-BM) Base Mount Bracket



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt
2.00	1.34	.50	.670	.440	.25	.24	.297	.740	.19	1.99	.062	1.75	.74	.350	.205	.125	.125	grams
50.80	34.04	12.70	17.02	11.18	6.35	6.10	7.54	18.80	4.83	50.55	1.57	44.45	18.80	8.89	5.21	3.18	3.18	59.8

Marking Drawing







**MSP2T-18-BM+
Base Mount Option**



MSP2T-18XL+ MSP2T-18-PM+ MSP2T-18-BM+

Typical Performance Data

FREQ. (MHz)	ON INSERTION LOSS (dB)		OFF ISOLATION (dB)		VSWR, IN (:1)		VSWR, (J1,J2) (:1)	
	IN-J1	IN-J2	IN-J1	IN-J2	De-Energized	Energized	De-Energized	Energized
10.00	0.00	0.00	92.40	95.82	1.00	1.00	1.00	1.00
100.00	0.01	0.01	92.57	102.75	1.00	1.01	1.01	1.00
1000.00	0.04	0.04	98.17	101.65	1.01	1.02	1.01	1.01
2000.00	0.06	0.06	103.54	95.79	1.03	1.04	1.04	1.02
3000.00	0.08	0.07	97.19	97.25	1.05	1.07	1.07	1.06
4000.00	0.09	0.08	92.71	94.48	1.08	1.09	1.10	1.08
5000.00	0.11	0.10	85.50	98.00	1.11	1.12	1.11	1.10
6000.00	0.13	0.11	93.58	94.07	1.14	1.15	1.15	1.14
7000.00	0.14	0.14	98.28	89.40	1.14	1.15	1.15	1.15
8000.00	0.14	0.14	106.76	91.02	1.13	1.12	1.12	1.13
9000.00	0.14	0.14	100.25	89.95	1.10	1.07	1.07	1.10
10000.00	0.15	0.14	89.20	91.80	1.06	1.04	1.04	1.07
11000.00	0.16	0.15	84.01	82.51	1.05	1.04	1.05	1.07
12000.00	0.16	0.17	96.22	88.82	1.07	1.05	1.04	1.08
13000.00	0.17	0.18	88.01	86.27	1.12	1.08	1.06	1.10
14000.00	0.20	0.20	83.33	87.28	1.16	1.08	1.08	1.16
15000.00	0.22	0.21	82.33	81.73	1.17	1.09	1.10	1.17
16000.00	0.23	0.21	80.17	85.38	1.19	1.10	1.12	1.20
17000.00	0.24	0.24	79.28	75.47	1.20	1.09	1.09	1.20
18000.00	0.28	0.27	78.01	79.03	1.20	1.10	1.07	1.21



Additional Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

