

Frequency Synthesizer

KSN-4261A-119+

50Ω 4152 to 4261 MHz

The Big Deal

- Low phase noise and spurious
- Robust design and construction
- Small size 0.80" x 0.58" x 0.24"



CASE STYLE: DK1182

Product Overview

The KSN-4261A-119+ is a Frequency Synthesizer, designed to operate from 4152 to 4261 MHz for digital radio application. The KSN-4261A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.24") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Low phase noise and spurious: <ul style="list-style-type: none">• Phase Noise: -98 dBc/Hz typ. @ 10 kHz offset• Comparison Spurious: -90 dBc typ.• Reference Spurious: -97 dBc typ.	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Robust design and construction	To enhance the robustness of KSN-4261A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.
Small size, 0.80" x 0.58" x 0.24"	The small size enables the KSN-4261A-119+ to be used in compact designs.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC VCO=+5V, VCC PLL=+5V)
- Small size 0.80" x 0.58" x 0.24"



PRICE: \$29.95 ea. QTY (1-9)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

- Digital radio

The KSN-4261A-119+ is a Frequency Synthesizer, designed to operate from 4152 to 4261 MHz for digital radio application. The KSN-4261A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.24") to shield against unwanted signals and noise. To enhance the robustness of KSN-4261A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.

Block diagram of a PLL system:

- External FREF XTAL** provides the **REF In** signal to the **PLL** block.
- The **PLL** block contains:
 - 1/R R COUNTER**
 - K Φ Phase Detector / Charge Pump**
 - 1/N N COUNTER**
- The PLL is powered by **VCC PLL** and has control pins: **LE**, **DATA**, **CLOCK**, and **LOCK DET**.
- The PLL output **RFinA** is connected to the **LOOP FILTER**.
- The **LOOP FILTER** output is connected to the **VCO**.
- The **VCO** is powered by **VCC VCO** and has a control pin **VP**.
- The **VCO** output is connected to the **SPLITTER**.
- The **SPLITTER** output is connected to the **RF Out** signal.
- A **GND** pin is also shown on the top supply line.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



Mini-Circuit **The Design Engineers Search Engine finds the model you need, Instantly** • For detailed performance specs & shopping online see www.minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp.



REV. OR
M126018
EDR-8164F1
KSN-4261A-119+
Category-A1
RAV
100322
Page 2 of 11

Electrical Specifications (over operating temperature -40°C to +85°C)

Parameters		Test Conditions	Min.	Typ.	Max.	Units
Frequency Range		-	4152	-	4261	MHz
Step Size		-	-	250	-	kHz
Settling Time		Within ± 1 kHz	-	5	-	mSec
Output Power		-	+1.0	+4.5	+7.0	dBm
SSB Phase Noise	@ 100 Hz offset	-	-	-70	-	dBc/Hz
	@ 1 kHz offset	-	-	-71	-64	
	@ 10 kHz offset	-	-	-98	-93	
	@ 100 kHz offset	-	-	-122	-117	
	@ 1 MHz offset	-	-	-142	-136	
Reference Spurious Suppression		Ref. Freq. 10 MHz	-	-97	-70	dBc
Comparison Spurious Suppression		Step Size 250 kHz	-	-90	-70	
Non - Harmonic Spurious Suppression		-	-	-90	-	
Harmonic Suppression		-	-	-24	-18	
VCO Supply Voltage		5.00	4.75	5.00	5.25	V
PLL Supply Voltage		5.00	4.75	5.00	5.25	
VCO Supply Current		-	-	34	41	mA
PLL Supply Current		-	-	16	22	
Reference Input (External)	Frequency	10 (sine wave)	-	10	-	MHz
	Amplitude	1	-	1	-	V _{P-P}
	Input impedance	-	-	100	-	K Ω
	Phase Noise @ 1 kHz offset	-	-	-140	-	dBc/Hz
RF Output port Impedance		-	-	50	-	Ω
Input Logic Level	Input high voltage	-	2.55	-	-	V
	Input low voltage	-	-	-	0.55	V
Digital Lock Detect	Locked	-	2.40	-	3.20	V
	Unlocked	-	-	-	0.40	V
Frequency Synthesizer PLL		-	ADF4106			
PLL Programming		-	3-wire serial 3V CMOS			
Register Map @ 4261 MHz	F_Register	-	(MSB) 100111111000000010010011 (LSB)			
	N_Register	-	(MSB) 001000100001010001010001 (LSB)			
	R_Register	-	(MSB) 000100000000000010100000 (LSB)			

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	5.4V
PLL Supply Voltage	5.8V
VCO Supply Voltage to PLL Supply Voltage	-0.3V to +5.8V
Reference Frequency Voltage	-0.3Vmin, +3.2Vmax
Data, Clock, LE Levels	-0.3Vmin, +3.2Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

Typical Performance Data

FREQUENCY (MHz)	POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURENT (mA)		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
4152	5.12	4.21	3.73	32.47	34.84	36.27	15.02	16.03	17.13
4156	5.10	4.22	3.71	32.47	34.83	36.27	15.03	16.05	17.14
4174	5.10	4.42	3.65	32.43	34.79	36.26	15.04	16.06	17.15
4192	5.32	4.58	3.77	32.38	34.77	36.23	15.03	16.05	17.14
4210	5.48	4.51	3.92	32.35	34.75	36.22	15.04	16.06	17.14
4228	5.41	4.41	3.91	32.34	34.73	36.22	15.05	16.06	17.15
4246	5.35	4.46	3.76	32.30	34.69	36.21	15.05	16.07	17.16
4261	5.40	4.63	3.72	32.25	34.66	36.20	15.05	16.07	17.16

FREQUENCY (MHz)	HARMONICS (dBc)					
	F2			F3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
4152	-36.37	-30.95	-30.29	-23.67	-24.93	-28.54
4156	-36.24	-30.95	-30.44	-23.67	-25.31	-28.88
4174	-34.69	-32.27	-30.53	-24.30	-24.69	-28.97
4192	-36.57	-30.67	-31.16	-24.74	-26.00	-31.21
4210	-33.31	-31.28	-30.57	-25.36	-25.86	-31.66
4228	-35.48	-31.51	-31.90	-25.80	-25.15	-31.36
4246	-35.80	-31.17	-32.11	-25.10	-27.10	-32.44
4261	-34.53	-32.56	-31.75	-26.53	-27.25	-32.28



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+25°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
4152	-72.33	-71.82	-99.53	-123.54	-143.25
4156	-69.63	-71.48	-99.75	-123.37	-143.19
4174	-69.30	-71.14	-99.19	-122.88	-142.88
4192	-68.57	-71.20	-98.35	-122.24	-142.45
4210	-73.70	-71.89	-98.73	-122.32	-142.27
4228	-72.54	-70.17	-98.82	-122.09	-142.46
4246	-70.30	-70.50	-98.50	-121.54	-140.93
4261	-69.87	-71.39	-97.84	-120.79	-140.21

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	-45°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
4152	-67.15	-70.94	-97.38	-121.84	-140.71
4156	-66.88	-69.89	-97.25	-122.06	-141.14
4174	-66.55	-71.27	-97.57	-122.06	-141.63
4192	-70.04	-72.04	-97.17	-121.88	-141.87
4210	-69.14	-71.31	-97.30	-121.80	-142.25
4228	-68.65	-71.18	-97.69	-121.73	-142.37
4246	-70.73	-71.94	-97.64	-122.04	-142.28
4261	-67.71	-71.71	-97.65	-121.52	-141.98

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+85°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
4152	-68.44	-71.64	-98.47	-122.91	-143.04
4156	-70.99	-71.15	-98.24	-122.87	-143.09
4174	-71.11	-70.40	-98.33	-122.71	-142.82
4192	-71.24	-69.61	-98.09	-122.10	-141.87
4210	-70.13	-69.80	-97.49	-121.02	-141.05
4228	-70.04	-68.91	-97.30	-120.49	-140.85
4246	-67.84	-67.68	-97.65	-120.34	-140.30
4261	-67.99	-68.36	-97.45	-120.08	-140.10



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

COMPARISON SPURIOUS ORDER	COMPARISON SPURIOUS @Fcarrier 4152MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @Fcarrier 4207MHz+(n*Fcomparison) (dBc) note 1			COMPARISON SPURIOUS @Fcarrier 4261MHz+(n*Fcomparison) (dBc) note 1		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-109.39	-111.01	-113.65	-108.78	-110.66	-117.84	-115.16	-106.25	-109.68
-4	-106.31	-106.73	-112.04	-106.75	-108.84	-116.35	-110.41	-104.78	-108.55
-3	-101.27	-102.89	-108.04	-103.76	-106.58	-113.97	-107.03	-101.82	-104.68
-2	-93.75	-97.32	-102.74	-102.09	-101.28	-105.68	-100.85	-97.25	-100.50
-1	-80.27	-83.54	-90.12	-91.64	-95.84	-94.97	-88.33	-86.52	-89.04
0 note 2	-	-	-	-	-	-	-	-	-
+1	-80.81	-83.93	-92.11	-94.98	-94.57	-93.22	-87.70	-86.59	-88.68
+2	-94.71	-97.53	-104.71	-104.78	-101.22	-103.53	-100.10	-97.20	-98.41
+3	-101.75	-104.62	-110.20	-106.50	-105.19	-110.22	-107.22	-102.21	-102.69
+4	-106.90	-107.93	-114.01	-108.53	-108.54	-111.84	-110.18	-105.54	-104.40
+5	-110.62	-113.53	-117.32	-110.16	-110.04	-114.98	-114.22	-107.14	-107.62

Note 1: Comparison frequency 250 kHz

Note 2: All spurs are referenced to carrier signal (n=0).

REFERENCE SPURIOUS ORDER	REFERENCE SPURIOUS @Fcarrier 4152MHz+(n*Frefernce) (dBc) note 3			REFERENCE SPURIOUS @Fcarrier 4207MHz+(n*Frefernce) (dBc) note 3			REFERENCE SPURIOUS @Fcarrier 4261MHz+(n*Frefernce) (dBc) note 3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-126.00	-130.43	-124.65	-128.96	-126.12	-130.42	-125.01	-122.88	-126.81
-4	-122.03	-120.28	-122.34	-121.33	-124.65	-124.01	-120.86	-122.33	-123.85
-3	-131.31	-130.54	-128.61	-129.72	-132.02	-127.83	-131.50	-129.70	-130.78
-2	-104.42	-107.79	-109.54	-103.37	-108.98	-110.01	-102.68	-103.96	-107.81
-1	-97.18	-95.83	-96.17	-95.36	-92.97	-93.19	-95.11	-92.13	-94.08
0 note 4	-	-	-	-	-	-	-	-	-
+1	-103.23	-102.05	-96.59	-101.53	-99.77	-96.09	-100.95	-97.48	-97.27
+2	-99.85	-101.73	-103.72	-100.13	-102.40	-103.63	-101.07	-101.53	-104.46
+3	-125.30	-122.56	-124.50	-124.54	-121.71	-126.27	-128.13	-124.83	-126.49
+4	-115.21	-115.99	-116.41	-117.36	-119.54	-131.66	-118.02	-117.46	-117.51
+5	-123.40	-124.36	-124.55	-123.21	-121.27	-131.88	-123.95	-126.35	-127.84

Note 3: Reference frequency 10 MHz

Note 4: All spurs are referenced to carrier signal (n=0).



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661






The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Typical Performance Curves



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.


PHASE NOISE @ 100Hz offset




PHASE NOISE @ 1kHz offset




PHASE NOISE @ 10 kHz offset



PHASE NOISE @ 100 kHz offset



PHASE NOISE @ 1MHz offset









IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Pin Configuration




Pin Connection


Pin Number	Function
1	VCC PLL
2	GND
3	REF IN
4	GND
5	VCC VCO
6	GND
7	RF OUT
8	GND
9	LOCK DET
10	CLOCK
11	DATA
12	LE
13	GND
14	GND

Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.



Device Marking



Additional Detailed Technical Information

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: DK1182

Tape & Reel: TR-F28

Suggested Layout for PCB Design: PL-249

Evaluation Board: TB-567+

Environment Ratings: ENV03T2



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.