



5300 Beethoven Street, Los Angeles, CA 90066
TEL: (310)306-5556 • FAX: (310)577-9887
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5164-900

0.8 - 4.2 GHz
80 WATTS
LINEAR POWER RF AMPLIFIER

Solid State Broadband High Power RF Amplifier

The 5164-900 is a 80 Watt broadband amplifier that covers the 0.8 – 4.2 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5164-900 comes with an extended multiyear warranty.

CIRCUIT PROTECTIONS

◇ Thermal Overload

FEATURES

- ◇ R – Rear Panel Connectors
 - ◇ RE – R Model W/ Controller Option
 - ◇ Customer Specific Front Panel
 - ◇ Rear Panel Mounted Dsub9-Female for External RF Enable / Standby Control
- NOTE: Pin **5** is GND, Pin **1** is the Control Line.
- IF Pin 1: OPEN - RF Standby Condition (Nominal Gain - 30dB min.)
 - IF Pin 1: GND - RF Enabled (Amplifier in Normal Operation) (< 100mA to Activate)

	Parameter	Specification @ 25° C
<u>Electrical</u>		
1	Frequency Range	0.8 – 4.2 GHz
2	Saturated Output Power	80 Watts typical
3	Power Output @ 1dB Comp.	60 Watts min
4	Small Signal Gain	+56 dB min
5	Small Signal Gain Flatness	± 2.5 dB max
6	IP ₃	+47 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 60 Watts
9	Spurious Signals	> -60 dBc typical @ 60 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	1200 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	+10 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	A/AB
<u>Mechanical</u>		
16	Dimensions	19" x 8.75" x 26"
17	Weight	80 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
<u>Environmental</u>		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.