

AD-HN8HN8	HN Jack To HN Jack	50Ω												
Technical drawing of the AD-HN8HN8 connector. It shows a side view with two threaded sections on either side of a central body. The threads are labeled 3/4-20UNEF-2A. The total length of the central body is indicated as 42 (1.654). Typical VSWR <table border="1"> <tr> <th>Part Number</th><th>1 Ghz</th><th>2 Ghz</th></tr> <tr> <td>AD-HN8HN8</td><td>1.22</td><td>1.3</td></tr> </table>			Part Number	1 Ghz	2 Ghz	AD-HN8HN8	1.22	1.3						
Part Number	1 Ghz	2 Ghz												
AD-HN8HN8	1.22	1.3												
<table border="1"> <thead> <tr> <th>Parts</th><th>Material</th><th>Plating (Micro-inch)</th></tr> </thead> <tbody> <tr> <td>Contact Pin</td><td>Beryllium Copper</td><td>Silver Plating 150 Over Copper 50</td></tr> <tr> <td>Insulator</td><td>Teflon</td><td></td></tr> <tr> <td>Body</td><td>Brass</td><td>Nickel 100 Over Copper 50</td></tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Silver Plating 150 Over Copper 50	Insulator	Teflon		Body	Brass	Nickel 100 Over Copper 50
Parts	Material	Plating (Micro-inch)												
Contact Pin	Beryllium Copper	Silver Plating 150 Over Copper 50												
Insulator	Teflon													
Body	Brass	Nickel 100 Over Copper 50												
Weight: 12.8 g														

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.