

Product Features

- PCS, WiMAX & WiFi Freq Range
- 800-960/1710-2500 MHz
- 50W power handling
- High Gain, 2,5 dBi Omni
- Indoor Cone Mount (ICM) Antenna
- SMA Male, SMA Female, N Female & TNC Male



Specifications ⁽¹⁾

Parameter	Value	Units	Description
Minimum Frequency	800-960	MHz	
Maximum Frequency	1710-2500	MHz	
Impedance	50	Ohms	
Maximum Gain	2,5	dBi	
Polarization	Vertical		
Max Input Power	50	Watts	
Maximum VSWR	1.4	ratio	
Antenna Height	90	mm	3.54 Inches
Base Diameter	170	mm	6.7 Inches
Weight	250	g	.55 lbs
Lightning Protection			DC Ground
Cable Length	254	mm	10 inches RG58
Temperature Range	-40 to +60	Deg C	

Ordering Information

Part Number	Description
PE51098	800-960/1710-2500 MHz 2,5 dBi Gain ICM Dome Antenna with 10 inches RG58 coaxial cable attached with connector choice below
PE51098-1	PE51106 Terminated with SMA Male
PE51098-2	PE51106 Terminated with SMA Female
PE51098-3	PE51106 Terminated with N Female
PE51098-4	PE51106 Terminated with TNC Male

(1) Pasternack reserves the right to change specifications or information without notice.

(2) All specification values are "typical"