

# AMP2006

## SOLID STATE HIGH POWER AMPLIFIER

### FEATURES

Rack mounted system  
Class AB linear LDMOS design  
Instantaneous wide bandwidth  
Suitable for all modulations standards  
Built-in protection circuits  
High reliability and ruggedness



### ELECTRICAL SPECIFICATIONS

| Parameter                    | Specification  | Notes                              |
|------------------------------|----------------|------------------------------------|
| Operating Frequency Range    | 20 - 1000 MHz  |                                    |
| Power Output                 | 50 Watt Min    | Saturated CW                       |
| Power Gain                   | 47 dB Min      |                                    |
| Power Gain Flatness          | 3.0 dB p-p Max |                                    |
| Input Return Loss            | 10 dB Min      | Relative to 50 Ohm                 |
| 2-Tone Intermodulation (IMD) | >30 dBc Typ    | 37dBm/Tone, $\Delta = 1\text{MHz}$ |
| Harmonics                    | >25 dBc Typ    | At Rated Pout                      |
| Non Harmonics Spurious       | 60 dBc Min     | Non Harmonics                      |
| Operating Voltage            | 100 - 240 VAC  |                                    |
| Power Consumption            | 350 Watt Max   | At rated Pout                      |
| Max Input Power              | +8 dBm         | Without damage                     |
| Load VSWR Protection         | $\infty : 1$   |                                    |

### ENVIRONMENTAL CHARACTERISTICS

| Parameter                     | Specification | Notes            |
|-------------------------------|---------------|------------------|
| Operating Ambient Temperature | 0 to +50 °C   |                  |
| Storage Temperature           | -40 to +85 °C |                  |
| Relative Humidity             | 5 to 95 %     | Non Condensation |

### MECHANICAL SPECIFICATIONS

| Parameter                                                                     | Specification                                       | Notes                        |
|-------------------------------------------------------------------------------|-----------------------------------------------------|------------------------------|
| Dimensions W x H x D                                                          | 430 x 88 x 562 mm                                   | 2U                           |
| Weight                                                                        | 10 kg.                                              |                              |
| RF Connectors In/Out                                                          | Type-N Female                                       |                              |
| AC Power / Interface Connector                                                | IEC 60320-C14 / 9-Pin D-Sub                         |                              |
| Cooling                                                                       | Built in Fan Cooling                                |                              |
| OPTIONAL: Digital Monitor & Control<br>FWD, REV, VSWR, GAIN, ALC, V & I, TEMP | Ethernet RJ-45 TCP/IP, RS422/485, GPIB<br>Interface | Remote Bluetooth application |

# AMP2006 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

