


SPECIFICATIONS

Frequency Range: 130–550 MHz
 Insertion Loss: 0.4dB Max.
 Isolation: 20dB Min.
 VSWR: 1.15:1 Max.
 Amplitude Balance: ± 0.2 dB Max.
 Phase Balance: ± 2 Deg. Max.
 Power Handling: 30W (Load vswr at 1.2)


MATERIAL: DRAWN: Pailoon Luekhamhan DATE: 02-16-1998 APPROVED: T. Nguyen DATE: 02-16-1998		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A SHEET: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR (mm) (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.005$ ANGLE: $\pm 1/2^\circ$ THIRD ANGLE PROJECTION		DRAWING TITLE: 2-WAY POWER DIVIDER PART NO.: PS2-88 CAGE CODE: 022L5 SIZE: A REV: N/A DO NOT SCALE THE DRAWING
		DWG NO.: 08081		

Frequency Range: 130–550 MHz
 Insertion Loss: 0.4dB Max.
 Isolation: 20dB Min.
 VSWR: 1.15:1 Max.
 Amplitude Balance: ± 0.2 dB Max.
 Phase Balance: ± 2 Deg. Max.
 Power Handling: 30W (Load vswr at 1.2)

DRAWN: Paiboon Luekhamhan	DATE: 02-16-1998
APPROVED: T. Nguyen	DATE: 02-16-1998



PROPRIETARY NOTICE:
THE INFORMATION IN THIS DRAWING IS PROPRIETARY
AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN
PERMISSION FROM MICROWAVE COMMUNICATIONS



DRAWING TITLE:

PART NO.	
----------	--

	CAGE CODE:
--	------------

REV:	N/A
------	-----

DO NOT SCALE THE DRAWING

SHEET: N/A

80881