

75 Ohm F Male Right Angle Connector Crimp/ Solder Attachment For RG6-CATV



TECHNICAL DATA SHEET

PE44320

75 Ohm F Male Right Angle Connector Crimp/Solder Attachment For RG6-CATV

Configuration

Connector F Male
Connector Interface Type RG6-CATV
Cable Attachment Method (Shield/Contact) Crimp/Solder
Body Style Right Angle

Electrical Specifications

Impedance, Ohms 75

Mechanical Specifications

Size

 Length, in [mm]
 0.87 [22.1]

 Width/Dia., in [mm]
 0.438 [11]

 Height, in [mm]
 1 [25.4]

 Weight, lbs [g]
 0.011 [4.99]

Connector

Type F Male
Contact Material and Plating Brass, Gold
Coupling Nut Material and Plating Brass, Nickel
Hex Size, in. 3/8
Torque, in-lbs [Nm] 5 [0.57]
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/f-male-standard-rg6-catv-connector-pe44320-p.aspx

75 Ohm F Male Right Angle Connector Crimp/Solder Attachment For RG6-CATV from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44320 CAD Drawing
75 Ohm F Male Right Angle Connector Crimp/Solder Attachment For RG6-CATV

